



## <u>General</u>

The Flange Seals FL01A is a simple designed assymetric seal for a wide range of static applications. Common sealing edge on the gap side for improved sealing performance.

## **Features**

- $\Rightarrow$  Especially designed for pressure from outside.
- $\Rightarrow$  Simple seal design maintain low costs.
- ⇒ Variable dimesions to be used also in special dimensioned grooves.
- $\Rightarrow$  Sealing over a wide range of pressures, temperatures and tolerances.
- $\Rightarrow$  Wide application ranges.
- $\Rightarrow$  Simple mounting.
- $\Rightarrow$  Compact and simple grooves.
- $\Rightarrow$  Easy and cost saving constructions possible.

## **Application**

Static sealing (e.g. flanges)

## **Installation**

Snap-in installation

Seal housing recommendation			Profile description
Tolerances	[mm]		
L < 10mm	+ 0.2		
L ≥10mm	+ 0.3		
ø NA	H8		Elongo Sool
ø NI	f7		Flange Seal
			•
Surface roughness	Rtmax [µ]	Ra [µ]	
Bottom of groove	≤ 6.3	≤ 1.6	<b>FL01A</b>
Face of groove	≤ 15	≤ 3	
Sliding surface	Rtmax [µ]	Ra [µ]	
onding our labo	≤ 6,3	≤ 1,6	

22.April.2009