



# MULTIFIT TYPE

## BS STANDARD CONNECTIONS



### M20512

BSP FEMALE 60° CONE (THRUST-WIRE NUT) - BS5200 (DKR)



### M20513

BSP FEMALE 60° CONE (SLIP-ON NUT) - BS5200 (DKR)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS			
	DN	inch	dash		B	A	C	H1

PART. REF.	DN	inch	dash	T (BSP)	B	A	C	H1
M20512-03-02	5	3/16"	-03	1/8"-28	3,1	14,8	4,4	14
M20513-03-04	5	3/16"	-03	1/4"-19	4,0	16,5	5,4	19
M20512-04-02	6	1/4"	-04	1/8"-28	3,1	15,5	4,4	14
M20513-04-04	6	1/4"	-04	1/4"-19	4,0	17,0	5,4	19
M20513-04-06	6	1/4"	-04	3/8"-19	7,0	19,1	6,0	22
M20512-05-04	8	5/16"	-05	1/4"-19	4,1	17,5	5,4	19
M20513-05-06	8	5/16"	-05	3/8"-19	7,0	19,1	6,0	22
M20513-05-08	8	5/16"	-05	1/2"-14	5,5	20,0	6,5	27
M20512-06-04	10	3/8"	-06	1/4"-19	4,1	18,1	5,4	19
M20513-06-06	10	3/8"	-06	3/8"-19	7,0	19,6	6,0	22
M20513-06-08	10	3/8"	-06	1/2"-14	9,3	20,0	6,5	27
M20512-08-06	12	1/2"	-08	3/8"-19	7,1	20,9	6,0	22
M20513-08-08	12	1/2"	-08	1/2"-14	9,3	20,4	6,5	27
M20512-08-10	12	1/2"	-08	5/8"-14	12,1	21,9	10,2	28
M20512-08-12	12	1/2"	-08	3/4"-14	15,0	23,4	9,0	32
M20512-10-08	16	5/8"	-10	1/2"-14	12,5	22,0	6,5	27
M20512-10-10	16	5/8"	-10	5/8"-14	12,5	21,7	10,2	28
M20512-10-12	16	5/8"	-10	3/4"-14	15,0	23,2	9,0	32
M20512-12-12	19	3/4"	-12	3/4"-14	15,0	24,5	9,0	32
M20512-12-16	19	3/4"	-12	1"-11	19,8	26,0	10,5	38
M20512-16-16	25	1"	-16	1"-11	19,8	27,3	10,5	38